In this document

- How to configure Wireless Internet Connection through UMT Wireless on Windows 7
- How to configure Wireless Internet Connection through UMT Wireless on Windows XP
- How to configure proxy on MS Internet Explorer
- How to configure proxy on Mozilla Firefox
- How to configure proxy on Google Chrome

How to configure wireless internet connection through UMT Wireless on Windows 7

- 1. Turn on Wi-Fi access on your laptop.
- 2. Right click on the Wi-Fi icon **m** in system tray on the left lower corner of the screen.
- 3. Select option Connect automatically and click select.
- 4. Press Alt and T simultaneously or click tools from File Menu. Click on Internet options.
- 5. Click on **Connections** tab.
- 6. Click on LAN Settings.
- 7. Select Use proxy server for LAN, In the Address field enter value 172.2.0.2 (for SBE & SST staff) and 172.2.0.6 (for rest of the staff) in Port field, enter value 8080 and select check box labeled as Bypass proxy server for local address.

NOTE: For the participants log on the proxy address 172.2.0.45 is used with the port value 8080.

Step 1. Right click on the Wi-Fi icon in system tray on the left lower corner of the screen and then click UMT-Wireless.	Step 2. Select option Connect automatically and click select.
Not connected Image: Connections are available Wireless Metwork Connection UMT-Wireless Open Network and Sharing Center	Not connected Image: Connections are available Wireless Network Connection UMT-Wireless Image: Connect and the second sec
▲ ► ● 8:13 PM 12/2/2011	▲ ■ → 8:33 PM 12/2/2011

Step 3. Press Alt and T simultaneously or click tools from File Menu. Click on Internet options.	Step 4. Click on Connections tab.	
India rife Mend. Click on internet options. Image Page < Safety < Tools	Internet Options General Security Privacy Content Connections rograms / Home page Image To create home page tabs, type each address on its ow about:blank Use current Use default Delete browsing history cookies, saved passwor and web form information. Delete Search Change search defaults. Tabs Settin Change how webpages are displayed in Settin Appearance OK OK Cancel	

Step 4. Click on LAN Settings.	Step 5. Select Use proxy server for LAN, In the Address field enter value 172.2.0.2 (SBE, SST, SEN & SLP) rest of other departments please type 172.2.0.6, in Port enter value 8080 and select check box labeled as Bypass proxy server for local address .
? × ity Privacy Content Connections Programs Advanced et up an Internet connection, click Setup D.	Local Area Network (LAN) Settings
Add Add VPN Remove	Automatic configuration Automatic configuration may override manual settings. To use of manual settings, disable automatic configuration. Automatically detect settings Use automatic configuration script
ngs if you need to configure a proxy Settings connection. al a connection rever a network connection is not present ial my default connection None Set default	Address Proxy server Proxy server Server Server Address: 172.2.0.2 Port: 8080
twork (LAN) settings do not apply to dial-up connections. LAN settings ings above for dial-up settings. OK Cancel Apply	OK

How to configure wireless internet connection through UMT Wireless on Windows XP

- 1. Turn on Wi-Fi access on your laptop or desktop, Click on **Start** and click on **Control Panel**.
- 2. Locate icon Network Connections and double click to open it.
- 3. In browse window locate your wireless connection if it is disabled then right click on it and select Enable.
- 4. Right click on the Wi-Fi icon 述 in system tray on the lower right corner of the screen.
- 5. Wireless Connection Wizard will open. Select **UMT-Wireless** from the list shown.
- 6. A warning message will appear. Select the option Connect Anyway
- 7. UMT-Wireless will be show as connected.
- 8. In Internet Explorer select Tools from File menu and select Internet options from drop down menu.
- 9. Select Connections tab and Click on LAN Settings.
- 10. Select Use proxy server for LAN, In the Address field enter value **172.2.0.2**, in **Port** field enter value **8080** and select check box labeled as **Bypass proxy server for local address**.



Step 3. In browse window locate your wireless connection if it is disabled then right click on it and select Enable.	Step 4. Right click on the Wi-Fi icon 💐 in system tray on the lower right corner of the screen.	
LAN or High-Speed Internet		
Local Area Connection Connected 3Com EtherLink XL 10/100 PCI		
Wireless Network Connection Disabled AT-WCL007 802.11 Status		
Create Shortcut		
Delete		
Rename		
Properties		
	9:36 AM	





Step 7. UMT-Wireless will be show as connected.				
((†))Wireless Netv	vork Connection		X	I
Network Tasks	Choose	e a wireless network		
💋 Refresh ne	twork list Click an ite information	m in the list below to connect to a wireles n.	ss network in range or to get more	
Set up a wi for a home	reless network or small office	UMT-Wireless Unsecured wireless network		
Related Tasks		This network is configured for open acc may be visible to others. You are curre	cess. Information sent over this network ently connected to this network. To	
Learn abou networking	t wireless	disconnect from this network, click Disc	connect below.	
Change the preferred r	e order of etworks			
Change ad settings	vanced			
	,		Disconnect	

Step 8. In Internet Explorer select Tools from File menu	Step 9. Select Connections tab and Click on LAN Settings.	
and Select internet options from drop down menu.		
Cannot find server - Microsoft Internet Explorer	Internet Options	
File Edit View Favorite Tools Belp	General Security Privacy Content Connections Programs Advanced	
🕞 Back 👻 🕥 👻 👔 Mail and News 🕨	To set up an Internet connection, click Setup	
Address e http://www.umt.edi Manage Add-ons	Dial-up and Virtual Private Network settings	
Synchronize Windows Undate	Add	
The page car	Remove	
	Choose Settings if you need to configure a proxy Settings	
The page you are looking to a superior of the page	Never dial a connection	
site might be experiencing technical difficulties, or	C Dial whenever a network connection is not present	
to adjust your browser settings.		
	Current None Set Default	
Please try the following:	Local Area Network (LAN) settings LAN Settings do not apply to dial-up connections.	
 Click the 🙀 Refresh button, or try again lat 	Choose Settings above for dial-up settings.	
 If you typed the page address in the Addressure that it is spelled correctly. 		
	OK Cancel Apply	

Step 9. Select Use proxy server for	or LAN, In the Address field enter valu	ue 172.2.0.2 (for SBE, SST, SEN & SLP) rest of ot	her
departments please type 172.2.0	.6,, in Port field enter value 8080 and	d select check box labeled as Bypass proxy serv	er
for local address.			
	Local Area Network (LAN) Settings	?	

LUCALAREA NELWORK (LAN) Settings
Automatic configuration Automatic configuration may override manual settings. To ensure the use of manual settings, disable automatic configuration.
Automatically detect settings
Use automatic configuration script
Address
Proxy server
Use a proxy server for your LAN (These settings will not apply to dial-up or VPN connections).
Address: 172.2.0.2 C Port: 8080 Address.
Bypass proxy server for local addresses
OK Cancel

Configuration of proxy server with Mozilla Fire Fox

NOTE: Google Chrome uses the configuration for MS. Internet Explorer. To configure Internet explorer please see